

**AMENDMENTS TO THE CLAIMS**

1. (Currently Amended) An illuminating apparatus ~~having~~ comprising:  
a pointer adapted to be turned around a rotary shaft,  
a display member positioned on a rear side of the pointer and adapted to be transmission  
illuminated,  
light sources positioned on a rear side of the display member and in the vicinity of the rotary  
shaft and adapted to illuminate the display member,  
a reflector positioned on the rear side of the display member and provided with a reflecting  
portion, and  
a light guide member positioned on the rear side of the display member and adapted to guide  
the light from the light sources to the rear side of the display member, characterized in that a hollow  
portion is formed between a rear surface of the display member and reflector, and  
an irradiation portion of the light guide member is adapted to apply the light, which is  
reflected on the reflecting portion and illuminates the display member, to the interior of the hollow  
portion being provided on the light guide member.

2. (Original) An illuminating apparatus having a pointer adapted to be rotated  
around a rotary shaft, a display member positioned on a rear side of the pointer and provided  
with a portion to be transmission illuminated, first light sources positioned on the rear side  
of the pointer and adapted to illuminate the pointer, second light sources positioned on a rear  
side of the display member and adapted to illuminate the portion to be transmission  
illuminated, a first light guide member adapted to guide the light from the first light sources  
to the pointer, and a second light guide member positioned on the rear side of the display  
member and adapted to guide the light from the second light sources to the rear side of the

display member, characterized in that the first light guide member and second light guide member are formed in one body.

3. (Original) A lighting system having a pointer adapted to be turned around a rotary shaft, a display member positioned on a rear side of the pointer and provided with a portion to be transmission illuminated, first light sources positioned on the rear side of the pointer and adapted to illuminate the pointer, second light sources positioned on a rear side of the display member and adapted to illuminate the portion to be transmission illuminated, a first light guide member adapted to guide the light from the first light sources to the pointer, a second light guide member positioned on the rear side of the display member and adapted to guide the light from the second light sources to the rear side of the display member, and a reflector positioned on the rear side of the display member and provided with a reflecting portion, characterized in that a hollow portion is formed between a rear surface of the display member and reflector, an irradiation portion adapted to apply the light, which is reflected on the reflecting portion and illuminates the display member, to the interior of the hollow portion being provided on the light guide members, the first light guide member and second light guide member being formed in one body.

4. (Original) An illuminating apparatus according to Claim 2, wherein the first light guide member and second light guide member are separated by a partition, a joint portion for connecting the first and second light guide members together being provided in a position opposed to the region of a dial which is not provided with a portion to be transmission illuminated of the display member.

5. (Original) An illuminating apparatus according to Claim 1, wherein the reflecting portion has a curved cross-sectional shape.

6. (Original) An illuminating apparatus according to Claim 1, wherein the reflecting portion has a cross-sectional shape obtained by forming a plurality of flat surfaces continuously at various angles.